

ECOLANDER SERIES

UTQG

TREADWEAR: 480
TRACTION: A
TEMPERATURE: B

SIZE	LOAD INDEX	PLY	SPEED RANGE	STANDARD RIM	TREAD DEPTH mm
215/70R16	99	-	T	6.5	9.6
225/70R16	101	-	T	6.5	9.6
235/70R16	104	-	T	7.0	9.6
245/70R16	106	-	T	7.0	9.6
☆ 245/70R16	111	-	T	7.0	9.6
255/70R16	109	-	T	7.5	9.6
265/70R16	111	-	T	8.0	9.6
265/65R17	110	-	T	8.0	9.6
265/70R17	113	-	T	8.0	9.6
275/65R17	113	-	T	8.0	11.6
215/75R15LT	106/103	8PR	S	6.0	11.6
225/75R15LT	108/104	8PR	S	6.0	11.6
235/75R15LT	110/107	8PR	S	6.5	11.6
31/10.50R15LT	109	6PR	S	8.5	11.6
215/85R16LT	115/112	10PR	S	6.0	11.6
225/75R16LT	115/112	10PR	S	6.0	11.6
235/85R16LT	120/116	10PR	S	6.5	11.6
245/75R16LT	120/116	10PR	S	7.0	11.6
265/70R16LT	121/118	10PR	R	8.0	11.6
265/75R16LT	123/120	10PR	S	7.5	11.6
285/75R16LT	126/123	10PR	R	8.0	11.6
245/75R17LT	121/118	10PR	S	7.0	11.6
265/70R17LT	121/118	10PR	S	8.0	11.6
285/70R17LT	121/118	10PR	S	8.5	11.6
315/70R17LT	121/118	10PR	R	9.5	11.6
275/65R18LT	123/120	10PR	S	8.0	11.6

Remark: ☆ = Reinforced